

192 BLOWER

		TOP PULLEY						
		4.35	4.10	3.85	3.60	3.35	3.10	2.85
ENGINE	350	4.7	5.7	7.0	8.4	9.8	11.5	13.0
	383	2.7	3.7	5.0	6.4	7.9	9.5	11.1
	400	1.9	3.0	4.2	5.6	7.1	8.7	10.2

250 BLOWER

		TOP PULLEY						
		4.35	4.10	3.85	3.60	3.35	3.10	2.85
ENGINE	427	5.4	6.8	8.3	10.0	11.7	13.5	15.4
	454	4.1	5.5	7.0	8.7	10.4	12.2	14.1
	502	2.4	3.8	5.3	7.0	8.7	10.5	12.4
	540	0.1	1.5	3.1	4.7	6.4	8.2	10.1

Stage 1 - 2 Blowers

6V-71 & 6-71 SMALL DIAMETER BLOWER

		DRIVE RATIO %												
		-25	-20	-15	-10	-5	0	5	10	15	20	25	30	35
ENGINE	350	3.9	5.1	6.4	7.6	8.8	10.1	11.3	12.6	13.8	15.0	16.3	17.5	18.6
	400	1.6	2.6	3.7	4.8	5.9	7.0	8.1	9.1	10.2	11.3	12.4	13.5	14.5
	454	-	0.1	1.2	2.3	3.4	4.5	5.6	6.6	7.6	8.6	9.6	10.6	11.6

6-71 LARGE DIAMETER BLOWER

		DRIVE RATIO %												
		-25	-20	-15	-10	-5	0	5	10	15	20	25	30	35
ENGINE	350	8.2	9.6	11.1	12.6	14.1	15.6	17.1	18.6	20.1	21.6	23.1	24.6	26.1
	400	5.2	6.5	7.8	9.1	10.4	11.7	13.0	14.3	15.6	16.9	18.2	19.5	20.8
	454	2.7	3.8	5.0	6.1	7.3	8.5	9.6	10.8	11.9	13.1	14.2	15.4	16.3
	502	0.8	1.9	3	4.1	5.2	6.3	7.4	8.4	9.4	10.4	11.4	12.4	13.4

8-71 BLOWER

		DRIVE RATIO %												
		-25	-20	-15	-10	-5	0	5	10	15	20	25	30	35
ENGINE	350	10.7	12.4	14.0	15.5	17.1	18.7	20.3	21.9	23.5	25.1	26.7	28.3	29.9
	400	7.6	9.0	10.3	11.7	13.2	14.6	16.0	17.3	18.7	20.1	21.5	22.9	24.3
	454	5	6.2	7.4	8.6	9.9	11.1	12.3	13.5	14.7	16.0	17.2	18.4	19.6
	502	3	4.2	5.3	6.4	7.5	8.6	9.7	10.8	12.0	13.1	14.2	15.3	16.4
	550	1.5	2.5	3.5	4.5	5.6	6.6	7.6	8.6	9.6	10.6	11.6	12.6	13.6

10-71 BLOWER

		DRIVE RATIO %												
		-25	-20	-15	-10	-5	0	5	10	15	20	25	30	35
ENGINE	454	6.3	7.6	8.9	10.2	11.5	12.8	14.1	15.4	16.7	18.0	19.4	20.7	22.0
	502	4.3	5.4	6.6	7.8	9.0	10.2	11.4	12.5	13.7	14.9	16.1	17.3	18.5
	550	2.6	3.7	4.8	5.8	6.9	8.0	9.1	10.2	11.3	12.3	13.4	14.5	15.6
	600	1.2	2.2	3.1	4.1	5.1	6.1	7.1	8.1	9.1	10.1	11.1	12.1	13.1
	650	-	0.9	1.8	2.7	3.6	4.5	5.4	6.3	7.3	8.2	9.1	10.0	10.9

12-71 BLOWER

		DRIVE RATIO %												
		-25	-20	-15	-10	-5	0	5	10	15	20	25	30	35
ENGINE	454	7.5	8.9	10.3	11.7	13.1	14.5	15.9	17.2	18.6	20.0	21.4	22.8	24.2
	502	5.4	6.7	7.9	9.2	10.4	11.7	12.9	14.2	15.4	16.7	18.0	19.3	20.6
	550	3.6	4.8	5.9	7.1	8.2	9.4	10.5	11.7	12.8	14.0	15.1	16.2	17.3
	600	2.1	3.2	4.2	5.3	6.3	7.4	8.4	9.5	10.5	11.6	12.6	13.6	14.6
	650	0.8	1.8	2.8	3.7	4.7	5.7	6.6	7.6	8.6	9.6	10.5	11.4	12.3

14-71 BLOWER

		DRIVE RATIO %												
		-25	-20	-15	-10	-5	0	5	10	15	20	25	30	35
ENGINE	454	8.8	10.3	11.7	13.2	14.7	16.1	17.6	19.1	20.5	22.0	23.5	25.0	26.4
	502	6.5	7.9	9.2	10.5	11.8	13.2	14.5	15.8	17.2	18.5	19.8	21.1	22.4
	550	4.7	5.9	7.1	8.3	9.5	10.7	12.0	13.2	14.4	15.6	16.8	18.0	19.2
	600	3.1	4.2	5.3	6.4	7.5	8.6	9.7	10.8	12.0	13.1	14.2	15.3	16.4
	650	1.7	2.7	3.8	4.8	5.8	6.8	7.9	8.9	9.9	10.9	12.0	13.0	14.0